



MODELS

KGV-MO-(2, 3, 4, 5, 6)-R

HIGH VOLUME GRAB-N-GO CASE FOR REMOTE CONDENSING UNIT

CASE HOLDS 33°F TO 40°F • FORCED AIR REFRIGERATION LED LIGHTING IN CANOPY AND UNDER SHELVES CASES CAN BE MULTIPLEXED















SELF CONTAINED	Model	Number of Doors	O.A. Length (inches)	Volume FT³	Total Amps	BTUS	Weight lbs		Crate Size (inches)		
							No Crate	With Crate	L"	W"	Н″
	KGV-MO-2-R	2 x 23-1/2	51-1/2	35.66	1.4	10458	456	661	54	36	85
	KGV-MO-3-R	3 x 23-1/2	75-3/8	53.41	2	15542	632	902	78	36	85
	KGV-MO-4-R	4 x 23-1/2	99-3/8	71.31	2.8	18436	912	1332	104	36	85
	KGV-MO-5-R	5 x 23-1/2	123-1/8	89.07	3.4	22861	1088	1563	126	36	85
	KGV-MO-6-R	6 x 23-1/2	147	106.82	4	27287	1264	1804	150	36	85

^{*} Note for other lengths please contact MVP

STANDARD FEATURES


Silver colored PVC coated steel front panel
CFC free injected foam insulation
PVC coated steel gray interior
Black steel kick plate
Foamed polystyrene black end panels
Height adjustable shelves can be tilted
Product stops on all shelves
Temperature and defrost regulated by a digital controller
Levelling feet

OPTIONAL FEATURES

Other colors available
Stainless steel exterior and / or interior
Additional shelves
Price tag molding
Product dividers
Joining Kit
Partition

WARRANTY

One year parts and labor with an additional four years on the compressor (part only)



NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R404a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-7/8" each. Ventilation grills at front and back cannot be blocked. B.T.U.'s are calculated at 14°F (evaporator) and 90°F (ambient). Floor drain must be provided. Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle. Cases must be hard wired – no plugs.



