

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

CUSTOMER'S CHOICE FOR A HOT KITCHEN Tested & Certified to Ambient Class of 100°F

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

UCR-SERIES UNDERCOUNTER UNITS

Versatile, compact model for undercounter and worktop applications for refrigerated storage of food product. Height is 34-5/8".

CABINET CONSTRUCTION

Heavy duty construction includes exterior stainless steel on front, sides, doors and grille. Cabinet back and bottom are galvanized steel. Interior liner is made of corrosion resistant aluminum. Interior thermometer is standard.

Cabinet is insulated with 2" thick foamed-in-place polyurethane insulation. Sub-top insulated with 1-1/2" foamed-in-place polyurethane insulation. Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Doors are equipped with a snap-in-place vinyl magnetic gasket for positive seal. Convenient, double pull style door handle is made of black anodized aluminum. 6" high casters are standard, 2 include brakes. An 8' cord set is provided with 115 volt models. Cabinet interior standard with 2 steel wire epoxy coated shelves per sec-

REFRIGERATION


Refrigeration system utilizes R134a refrigerant governed by a capillary tube system. Automatic (non-electric) condensate evaporator is provided. Interior forced-air system with high humidity evaporator coils, provides the ideal environment for food preservation.

ELECTRICAL

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

SPECIAL FEATURES

- Cartridge style door hinges provides positive seal & eliminates door sagging issues (excludes glass door and some special
- Optional 6" legs or 3" casters available



UNDERCOUNTER REFRIGERATOR **FOOD PREPARATION SERIES**

MODELS: UCR36A



UCR36A

ELECTRICAL CONNECTION

Units pre-wired at factory and include 8' long cord and plug set.



115/60/1











Available From:

Model Specified	Store#
Location	Quantity



Standard Undercounter Refrigerator Cabinet Models: UCR36A

MODEL	UCR36A
EXTERNAL DIMENSIONAL DATA	
Length Overall (inches) Length Overall (mm)	36" 914
Depth Overall (inches) - Less handle Depth Overall (mm) - Less handle	29 1/4" 743
Height Overall— on 6" casters (inches) Height Overall—on 6" casters (mm)	34 5/8" 880
Depth with Door Open 90 °	46 1/4"
Clear Door Opening (inches)	13 5/8" x 21 5/8"
Number of doors	2
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.) NET Capacity (Liters)	8.5 241
Internal Length Overall (inches) Internal Length Overall (mm)	32" 813
Internal Depth Overall (inches) Internal Depth Overall (mm)	20" 508
Internal Height Overall (inches) Internal Height Overall (mm)	23" 584
Number of shelves	4
ELECTRICAL DATA	
Full Load Amperes 115/60/1	3.3
ENERGY CONSUMPTION (KWH)	N/A*
REFRIGERATION DATA	
Horsepower	1/5
WEIGHT DATA	
Gross Weight (Crated lbs)	210
Gross Weight (Crated kg)	95











*Not available at time of printing

PLAN VIEWS

