





- 14" high-quality, heavy-duty straight-feed cooked meat slicers
- Designed for precision slicing of all kinds of cooked and cured meats
- Fitted with a double-feed carriage with a double articulating clamping arm holding any product firmly in place
- The TOP version provides even higher durability in terms of reduced maintenance costs with:
  - all knobs, handles, dials and feet in aluminum
  - a fully sealed and waterproof IP 67 switch, with stainless steel on/off buttons
  - no volt release prevents inadvertent reactivation after a power outage
  - complete stainless steel drive shaft assembly

## **Features**

- The special carriage allows you to slice any kind of cooked meat.
  The sharpener assembly is made entirely from aluminum, no plastic that may break with
- The tie rod assembly and all screws are made of stainless steel for longer life.
- The slide shaft is made of ground, chromed steel for a smoother operation.
- The high-quality bushings and ball bearings are self-lubricating.
   The dial thickness control cam system allows for an always precise cut.

- A safety cover is placed under the motor and the electrical components.
- The clamping arm features an exclusive heavy duty plastic protection to keep operator's hand at a safe distance from the blade while operating slicer.

### Sanitary

- Easy to clean aluminum alloy construction does not crack or stain.
- The screws are stainless steel and resist wear and oxidation.
- The carriage and the center plate are quickly removable without tools

# Specifications

Operation: Vertical feed.

Construction: Polished, anodized aluminum alloy. Knife 350:

14" (350 mm), one piece, chromium plated 100Cr6 forged

carbon steel blade.

Sharpener: Built-in, removable, two stone dual action.

Slice thickness: Infinitely variable up to 13/16"

Motor: 1/2 Hp (410 W), belt driven, fan cooled.

120V AC, 60Hz, 3.10 Amp. (220V, 50Hz available on request). Electrical: Plug and Cord: Attached, flexible, 3 wire SJT 18 AWG, 6'4" long cord,

NEMA 5-15P.

Switch: IP 67 controls with stainless steel on/off buttons.

No Voltage Release.








Increased gap between blade and machine body





Removable food pusher

Mantegna 350 BS TOP ROSSA









	Ø Blade	Motor	Cut thickness	Blade rpm	Carriage stroke	Норрег	А	В	С	D	E	F	G	Х	Υ	Н	W	Net weight	Shipping	Gross weight
	mm/inch	watt/Hp	inch.	rpm	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	inch.	lbs.	inch.	lbs.
Mantegna 350 BS TOP	350/14"	410-0,55	13/16"	216	123/16"	11 <sup>13/16</sup> " x 10 <sup>5/8</sup> "	187/16"	135/16"	26"	235/8"	207/8"	291/2"	281/8"	105/8"	101/16"	101/16"	101/16"	84	34 <sup>1/4</sup> " x 33 <sup>1/16</sup> " x 29 <sup>1/2</sup> "	117

