



REACH IN FREEZER D55F Bottom Mounted / 2-Solid Door



- i TECHNICAL SPECIFICATIONS**
- Voltage/Frequency 115V/60Hz
 - Refrigerant R290
 - Type of Defrost Automatic
 - Interior Material Stainless Steel
 - Exterior Material Stainless Steel
 - Temperature Range °F 0 ~ -8°F
 - Compressor Power (HP) 3/4
 - Nema Config. NEMA5-15P



PRODUCT FEATURES

- The compressor is mounted in the bottom for better heat evaporation.
- Digital temperature controls with LED display for precise adjustment and automatic defrosting system.
- Temperatures in the cabinet range from 0 to -8 degrees Fahrenheit
- Self closing doors with stay open feature.
- R290 Natural Refrigerant promotes faster cool down and efficient energy consumption.
- Epoxy coated wire shelves.
- Stainless steel interior & exterior, sealed interior floors, and rounded cabinet corners for easy cleaning.
- High quality coated stainless adjustable shelves prevent peel and rust.
- Lifetime warranty on hinges.
- Adjustable front locking casters.



HIGH QUALITY STAINLESS STEEL & ROBUST DESIGN



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey


1-800-931-8628

@ info@dukersusa.com


www.DukersUSA.com

DETAILS & SPECIFICATIONS

D55F



Side View



MODEL D55F	
Rated Voltage	115V
Rated Frequency	60Hz
Total Input Power	1250W
Total Current	11.8 A
Total Capacity	40.74 cu ft
Climatic Category	4-5
Protection Type	I
Design Pressure High Side	300 PSIG
Design Pressure Low Side	150 PSIG
Insulation Blowing Gas	C-Pentane
Refrigerant	R290/5.11 oz

MODEL	EXTERNAL DIMENSION WXDXH (INCHES)	PACKAGING DIMENSION WXDXH (INCHES)	PRODUCT NET WEIGHT	# OF SHELVES	40HQ CONTAINER CERT.
D55F	55 1/8 x 32 5/8 x 81 5/8	56 3/4 x 34 1/4 x 84 3/8	463 lbs	8	21



Los Angeles | San Francisco | Dallas
Houston | Florida | Chicago | New Jersey

1-800-931-8628

info@dukersusa.com

www.DukersUSA.com