





Voltage/Frequency 115V/60Hz Refrigerant R290 Type of Defrost Automatic Interial Material Stainless Steel Exterior Material Stainless Steel Temperature Range °F 33 ~ 41°F Compressor Power (HP) 1/5 Nema Config. NEMA5-15P

PRODUCT FEATURES

- The compressor is mounted in the back and placed in the coolest possible area; this makes it easily accessible for servicing.
- **B.B.** Digital temperature controls with LED display for precise adjustment and automatic defrosting system.
- * Temperatures in the cabinet range from 33 to 41 degrees Fahrenheit.
- Higher Resistance to dust, high quality condenser.
- ** R290 Natural Refrigerant promotes faster cool down and efficient energy consumption.
- Drawers hold 6" deep food pans (not included) with heavy-duty, high-capacity slide rails.
- Top prep rail comes equipped with 6" deep 1/6 plastic pans.
- \mathcal{T} 6" casters with lock for easy mobility.



HIGH QUALITY STAINLESS STEEL & **ROBUST DESIGN**




Los Angeles | San Francisco | Dallas Houston | Florida | Chicago | New Jersey 1-800-931-8628

(a) info@dukersusa.com


www.DukersUSA.com


DETAILS & SPECIFICATIONS

SALAD PREP TABLE DSP29-12M-D2-



@_





MODEL DSP29-12M-D2

Cutting Board Size	29 x 9		
Rated Voltage	115V		
Rated Frequency	60Hz		
Total Input Power	225W		
Total Current	2.0A		
Total Capacity	6.56 cu ft		
Climatic Category	4-5		
Protection Type	1		
Design Pressure High Side	300 PSIG		
Design Pressure Low Side	150 PSIG		
Insulation Blowing Gas	C-Pentane		
Refrigerant	R290/2.82 oz		

MODEL	EXTERNAL DIMENSION	PACKAGING DIMENSION	PRODUCT NET	# OF	40HQ
	WXDXH (INCHES)	WXDXH (INCHES)	WEIGHT	DRAWERS	CONTAINER CERT.
DSP29-12M-D2	29 1/8 x 31 1/2 x 45 3/4	33 3/8 x 35 7/8 x 48 3/8	202 lbs	2	56

Important: a) Width does not include 1/5" on each side for cutting board pins. b) Depth does not include 1" for rear bumpers. c) Height does include casters.















1-800-931-8628
© info@dukersusa.com
www.DukersUSA.com