

# **GLASS DOOR MERCHANDISER REFRIGERATOR**

SINGLE SWING DOOR

Project Name: \_

Model #:\_ \_\_\_ Quantity:\_\_\_\_

Available Warehouse:\_

Project Location:

#### **EM Series** Model: EMGR5





### **Refrigeration System**

Bottom mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.

- Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- · Large capacity, corrosion-resistant condenser and evaporator coils.
- Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters. High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

### **Cabinet Construction**

- · Heavy duty white coated steel interior / exterior.
- Open spaced interior with no walls between compartments.
- Stainless steel floor interior has rounded corners and detachable drain plug for ease of cleaning.
- 2.5" thick high density polyurethane insulation.
- Four height adjustable screw legs.

### Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

### Doors

- · Low emissivity double glass panes reflect UV rays for efficient cooling.
- Black PVC door frames. Self-closing with adjustable torsion system for a positive seal.
- Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, die-cast door handles.

### Shelving

- · Epoxy coated, steel wire shelves with airflow guard (see table for quantity).
- · Height adjustable stainless steel clips.

### **Temperature Control**

- Multi-function digital controller with easy to read LED display.
  Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- Audible overheat protection alarm for compressor and condenser coil.

### Options

- · Additional shelving.
- Wine rack (applies to model EMGR24 and EMGR24B).
- 5" or 3" swivel casters with locks on front set.
- · 3.5" 6" height-adjustable and interchangeable legs.



Please visit ou	r website for u	pdated Energy	Efficiency	information
-----------------	-----------------	---------------	------------	-------------

Ref/	Doors	Capacity		Shelves Refrigerant	city Shelves		HP Power	HP	Power Amos	AIDOS	Crated	Ext	erior Dimensi	ons
Frz/Dual	Doord	Cu. Ft.	20 oz. Bottles	nongorant	nonigorant	V-Hz-Ph	Weight		L		D	H*		
REF	1	5	60	2	R-290	1/5	115-60-1	2	190 lbs (86kg)	25" (635mm)	24.75" (629mm)	36" (914mm)		

(†) Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (↔) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.



# **GLASS DOOR MERCHANDISER REFRIGERATOR**

SINGLE SWING DOOR

# **EM Series**

# Model: EMGR5

# **DIMENSIONAL DATA**

	L	25" (635mm)
External Dimensions	D	24.75" (629mm)
	H*	36" (914mm)
Crated Weight		190 lbs. (86kg)
Doors/Drawers/Lids		1
Max Weight Support (	LBS)	-
STORAGE DATA		
Net Capacity Cu. Ft. 🏲		5
Shelves		2
Barrels		-
20 oz. Bottles		60
12 oz. Bottles		-
12 oz. Cans		-
8" Mugs		-
# of Pans (Top)		-
# of Pans (Drawer)		-
Dividers		-
Trays		-

## **ELECTRICAL DATA**

Voltage	115-60-1
Full Load Amperage	2A
Feed Wires with Ground	3
Cord Length	9ft
NEMA Plug Type	NEMA 5-15P

### **REFRIGERATION DATA**


Compressor Mounting	Bottom
Refrigerant	R-290
Compressor HP	1/5
BTU/HR <sup>†</sup>	1655

## KEY


D	Door	R	Refrigerator	
L	Lid	REF	Refrigerator	
H	Half Door	F	Freezer	
FD	Full Door	FRZ	Freezer	
SD	Solid Door	DUAL	REF/FRZ Combo	
GD	Glass Door	DR	Drawer	

	Elevation	Right	Plan	3D	Back
KCL					

PLAN VIEW



SIDE



FRONT

# ACCESSORIES & OPTIONS

Part Number	Description
Additional Shelving	Contact Everest Refrigeration for more information.
AJL03-00	Interchangeable Leg for Caster (Optional)
CASA3-01	3" Overall Height Caster Assembly - (2) Front (2) Rear
CASA5-01	5" Overall Height Caster Assembly - (2) Front (2) Rear
Left Hinged Door	Contact Everest Refrigeration for more information.

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (↔) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 4/18/2023