



MODELS

KFM-SC-(40, 50, 60, 80, 100, 120)-S KFM-SC-(40, 50, 60, 80, 100, 120)-R

CURVED GLASS SEAFOOD CASE DESIGNED FOR FRESH FISH

CASE HOLDS 33°F TO 40°F • LOW VELOCITY FORCED AIR REFRIGERATION MAINTAINS HIGH HUMIDITY TEMPERED SIDE GLASS AND REAR SLIDING DOORS • CASES CAN BE MULTIPLEXED CAN BE USED WITH OPTIONAL ICE PANS • CASES REQUIRE FLOOR DRAINS













SELF CONTAINED	Model	O.A. Length (inches)	Volume FT³	Electrical 115 Volts				NEMA	Weight lbs		Crate Size (inches)		
			Front	Compressor		LIGHTS	Total	115 V Plug	No	With			
				H.P	F.L.A	Fans HTRS	Amps	Flug	Crate	Crate	L"	W"	H″
	KFM-SC-40-S	40.4	12.35	3/8	8.4	0.95	9.35	5-15P	333	494	48	44	42
	KFM-SC-50-S	52.2	16.27	1/2	9.6	0.96	10.56	5-15P	377	560	59	44	42
	KFM-SC-60-S	60	18.88	1/2	9.6	1.08	10.66	5-15P	427	626	67	44	42
	KFM-SC-80-S	77.5	24.70	5/8	8.9	1.68	10.58	5-15P	531	794	85	44	42
	KFM-SC-100-S	101.4	32.54	3/4	16	1.81	17.81	5-15P	658	937	109	44	42
	KFM-SC-120-S	117	37.76	3/4	16	2.06	18.06		785	1160	124	44	42

	Kit No	For Model				
FS	KT025A	KFM-SC/SF/SO-40-S/R				
F	KT025B	KFM-SC/SF/SO-50-S/R				
🗒	KT025C	KFM-SC/SF/SO-60-S/R				
OPTIONAL ICE / FISH	KT025D	KFM-SC/SF/SO-80-S/R				
9	KT025E	KFM-SC/SF/SO-100-S/R				
g	KT025F	KFM-SC/SF/SO-120-S/R				

		O.A.	115 Volts		Weight lbs		
	Model	Length (inches)	Total Amps	B.T.U	No Crate	With Crate	
OTE	KFM-SC-40-R	40.4	0.5	2548	278	439	
REMOTE	KFM-SC-50-R	52.2	0.51	3015	322	505	
"	KFM-SC-60-R	60	0.63	3159	373	571	
	KFM-SC-80-R	77.5	0.78	4345	498	761	
	KFM-SC-100-R	101.2	0.91	5112	604	882	
	KFM-SC-120-R	117	1.16	5472	721	1093	

STANDARD FEATURES

Coated evaporator coil

Stainless steel frame

Stainless steel interior

Stainless steel rear work bench

Silver colored PVC coated steel front panel

CFC free injected foam insulation

Black steel kick plate

Foamed polystyrene black end panels

Tempered tilt foward front glass

Removable rear tempered glass sliding door

LED lighting in canopy

Temperature and defrost regulated by a digital controller

Slide out condensing unit on self-contained units

Anti condensing system for front glass

Digital thermometer

Levelling feet

OPTIONAL FEATURES

Ice/fish pan kit. See table above

Stainless steel exterior

Other colors available

Joining Kit

Partition

Scale stand with receptable

Cutting Board

Knife Support

Casters add 4-3/8" to height

Stainless steel legs are adjustable from 5-1/8" to 7-5/8"

WARRANTY

One year parts and labor with an additional four years on the compressor (part only)




Tel: 786.600.4687 / Toll Free: 844.218.8477

Fax: 786.661.4100

Tel: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / toll free: 877.453.8832

sales@mvpgroupcorp.com / mvpgroupcorp.com



NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R404a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-7/8" each. Ventilation grills at front and back cannot be blocked. B.T.U.'s are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle, Remote cases must be hard wired-no plugs.